

HIGH PERFORMANCE LOW SHRINK



Features & Benefits:

- Low Temperatures and less energy with high shrinkage
- Hot Slip after Shrinkage
- Great Clarity & Gloss
- Corrosion free and deposit free seals

Our HPS High Performance Low Shrink film is a 5 Layer polyolefin shrink film. The HPS is the happy medium between our RS and X film. It has the versatility to be used on both semi automatic & high speed applications. Works great with delicate products and heat sensitive products because it shrinks well under lower temperatures and is delicate enough not to distort the product. Gentle yet balanced shrink is what you can expect when using our HPS Low Shrink.

Applications & Options:

- Can be used with semi-automatic & high speed machinery (preferably used on Preferred Packaging equipment)
- Available in either single wound (HPS-s) or center-folded HPS-c)
- Reperforation available upon request

Storage:

Ideal storage temperatures below 32 Celsius/ 90 Fahrenheit. Prolonged exposure to temperatures above 32 Celsius may cause premature shrinkage and difficulty unwinding the film.

Disposal:

Our RS is a recyclable material that meets the requirements of SPI Recycle Code "4" and can be included in the LDPE recycle stream.

FDA/USDA & USPS Status

Our RS Regular Shrink complies with U.S. Food and Drug Administration (FDA) requirements under the Federal Food, Drug and Cosmetic Act as amended. Our RS Regular Shrink complies with FDA regulation 21 CFR 177.1520 – Olefin polymers, allowing use for articles that contact food, except for articles used for packaging or holding food during cooking.

